

15" TFT LCD Monitor

POS Application



Where Versatility Meets Flexibility

L15BX-JA

Configuration

L15BX-JA

| | |
|--------------------------|---|
| LCD Display | 15" TFT active matrix panel |
| Pixel Pitch | 0.297(H) x 0.297 (V) mm |
| Max. Resolution | XGA 1024 x 768 |
| Contrast Ratio | 400:1 (typical) |
| Brightness | 250 Cd/m ² (typical) |
| Response Time (Tr+ Tf) | 16 ms (typical) |
| Display Color | 16M |
| Effective Display Area | 304.1(H) x 228.1(V) |
| Viewing Angle (CR ≥ 10) | 120° (H) x 100° (V) |
| Backlight | CCFL x 2 |
| Lamp Life | 40,000(hr) |
| Stand Base | Tilt down: 0°, Tilt up: +37° |
| Input Signals | Analogue VGA |
| Signal Connector | Analog D-sub 15 pin (VGA) |
| | Digital N/A |
| Scan Frequency | H. scan 31~60KHz, V. scan 60~75Hz |
| Audio System | N/A |
| USB HUB | N/A |
| Touch Panel | Resistive/Capacitive - RS232 or USB A type (option) |
| Key Control | Power on/off with LED, Menu, Select, Adjustment (+, -) |
| Operating Condition | Temperature 5°C-35°C (41°F-95°F) |
| | Humidity 20%-80% (no condensation) |
| | Altitude To 10,000 feet |
| Storage Condition | Temperature -20°C-60°C (-4°F-140°F) |
| | Humidity 10%-90% (no condensation) |
| Power Adaptor | Universal power adaptor input AC 100 ~ 240V,50~60Hz; Output DC12V /3A |
| Power Consumption | 36W |
| Power Management | VESA DPMS standard |
| Dimensions (W x H x D) | 380 x 325.9 x 90 mm |
| Carton Dimensions | 440 x 458 x 216 mm |
| Weight (Net) | 4.3 Kg |
| Certification | C-UL, FCC, CE |

* Specifications are subject to change without notice.

Features :

- * High contrast color TFT LCD display supports resolution up to XGA 1024x768. Compatible with IBM VGA, VESA standards.
- * Support DDC1/2B for Plug & Play compatibility.
- * Advanced OSD control for picture quality adjustment.
- * Optional touch solutions.
- * Optional VESA mounting.
- * Hot key for AUTO adjustment.
- * Stable photo frame stand for touch solution.


Optional Accessories :

- * 3M 5 Wire resistive touch panel
- * ELO 5 Wire resistive touch panel
- * Anti-Glare tempered glass.
- * Anti-Glare tempered glass.
- * Customized touch solutions acceptable.

Ordering Information :

- * L15BX-LA VGA only

I/O Ports



Mechanical drawing

Unit : mm

